

Medium Flush Wood

NEXGEN-FYRE™ FIREPLACE INSERT

FIREPLACE
XTORDINAIR
FIREPLACEX.COM



The Medium Flush Wood Insert is shown with the Classic Arch™ Black Painted Face.

Mid-Sized Flush Insert that Provides Extraordinary Heat

The Medium Flush Wood NexGen-Fyre™ Insert converts a wasteful masonry or zero clearance fireplace into an excellent heat source that can provide reliable warmth at a fraction of the cost of electricity or oil. With a three-sided convection chamber and standard 180 CFM convection fan, this insert is designed to deliver the maximum heat output from the wood.

NexGen-Fyre™ takes our non-catalytic wood burning technology to the next level! With NexGen-Fyre™, primary and secondary combustion are harnessed to create the ultimate blended combustion system. This produces beautiful, balanced fires with double the BTU range, up to 50% greater heat output, and longer burn times than any other non-catalytic technology.

Available in Arched or Rectangular Door Models.

Medium Flush Wood

NEXGEN-FYRE™ FIREPLACE INSERT



SPECIFICATIONS

Emissions:	2.4 Grams Per Hour (Cord Wood)
Heating Capacity:*	1,200 to 2,000 Square Feet
EPA Tested BTU Range:	15,583 to 55,395 BTU's Per Hour
Real World BTUs:	
<i>EPA tests to determine BTU output are achieved with a single load of wood at each burn rate. At home, you are likely to add more wood to your insert to maintain your desired comfort level. By the simple process of loading your fireplace insert with additional wood, you could achieve up to a 20% higher heat output than established during EPA testing.</i>	
Efficiency:**	72% HHV
Maximum Burn Time:	Up to 10 Hours
Firebox Size:	2.2 Cubic Feet
Maximum Log Size:	24 Inches
Weight:	450 Pounds
Construction:	5/16" to 1/4" Steel Plate
Bypass Damper:	Yes
Glass Viewing Area:	22-5/8" W x 10" H (216 Sq. In. Arch, 227 Rect.)

*Heating capacity may vary depending on degree of home insulation, floor plan and ambient temperature zone of the area you live.

**As tested using B-415.1 using Cord Wood. HHV = High Heat Value.

OPTIONS

- Insert Wiring Kit
- **GREEN START** Igniter



DOOR FACE OPTIONS



*Classic Arch™ Face
Metallic Black paint finish
33-1/4" W x 23-3/4" H*



*Metropolitan™ Face
Metallic Black paint finish
33-3/8" W x 23-1/4" H*



*Shadowbox™ Face
Metallic Black paint finish
35-3/4" W x 22-1/8" H*

PUSH BUTTON START UP, THE GREATEST WOOD INSERT OPTION EVER!

Starting a fire in your wood insert is now as convenient as pushing a button. The patent-pending GreenStart® ignition system eliminates the mess of starting a fire with matches and newspaper, while increasing safety at the same time.

The GreenStart® system is perfect for refreshing a fire; simply open the bypass damper, add new fuel to the hot coals, push the button twice and the igniter adds enough air to ignite the hot coals. There is no need to blow on the coals or leave the door ajar, it's that easy!



Use your Smart
Phone QR Reader to
watch a video on the
GreenStart® Igniter



Scan For
Manual